



PLUGS & SOCKETS 2MM & 4MM

Plugs and sockets are having Brass Parts Bright Nickel plated and insulated by thermoplastic material.

PLUGS


GP2 - 2mm



GPB - 4mm



GP8 - 4mm




GP7 - 4mm



SOCKETS

GS2 - 2mm



GS5 - 4mm



General Specifications for Plugs and Sockets

| | Plugs and Sockets | |
|---------------------------------|-------------------|----------------|
| | 4mm. | 2 mm. |
| Current Rating | 10 Amps | 7 Amps |
| Insulation Resistance at 500 DC | 100 Mohms min | 100 Mohms min |
| Breakdown Voltage | 500 Vac 1 min. | 1000 Vac 1 min |
| Contact Resistance | 5 Mohms. max | 5 Mohms. max. |

| Ordering Information | |
|-----------------------------|----------------------------------|
| PLUGS 4 MM | |
| GPB | 300 BTR Plugs |
| GP-8 | Plug With Spring Wire 4 mm |
| GP-7 | Plug With Spring Wire Stack able |
| PLUGS 2 MM | |
| GP-2 | Plug With Spring Wire 2 mm |
| SOCKETS 4 MM | |
| GS-5 | Socket 4mm |
| SOCKETS 2 MM | |
| GS-2 | Socket 2mm |

Detail Drawing

