



TERMINALS

SPADE and BINDING POST

Spade Terminals

Spade Terminal has straight or side slot for connection to spindle of Terminal. It also has solder able lead. Insulating Handle is molded in Thermoplastic material available in Red & Black.

ST-1 STH-1



ST-2



ST-1-90D



Binding Post Terminals

Binding Post Terminals have heads with 4mm socket. (Except GT -3 which has 2mm socket hole). Cross holes are provided in the spindles for cable connection. Panel fitting is achieved by insulating bushes, two lock nuts and plain washer. All Brass parts are Bright Nickel plated.

GT-3



GTO-5




GT-10



GT-15



GT-30



SPECIFICATION

Parameter	ST - 1 ST - 2	STH - 1	GT - 3	GTO - 5 GTOL - 5	GT - 10	GT - 15	GT - 30
Current Rating	10A	15A	3A	5A	10A	15A	30A
Contact Resistance	5 Mohms Max	5 Mohms Max	10 Mohms Max	5 Mohms Max	5 Mohms Max	5 Mohms Max	5 Mohms Max
Flash over Voltage	1.2 K. V. min.	1.2 K. V. min.	1 K. V. min.	1.2 K. V. min.	1.2 K. V. min.	2 K. V. min.	2 K. V. min.
Insulation Resistance	1000 Mohms Max	1000 Mohms Max	1000 Mohms Max	1000 Mohms Max	1000 Mohms Max	1000 Mohms Max	1000 Mohms Max
Max. Working Temp.	70° C	70° C	70° C	70° C	70° C	100° C	100° C

Ordering Information	
SPADE TERMINALS	
ST-1	Spade Terminals Straight Cut
ST-2	Spade Terminals Side Cut
ST-1 90 DEGREE	Spade Terminals Straight Cut With 90 Degree Bend
BINDING POST TERMINALS	
GT-3	Terminal 3 Amp.
GTO-5	Terminal 5 Amp.
GTOL-5	Terminal 5 Amp. – Extra Long threaded Stem
GT-10	Terminal 10 Amp.
GT-15	Terminal 15 Amp.
GT-30	Terminal 30 Amp.

Detail Drawing

